

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only	Net Weight (lb) cylinder undercarriage only
L13010	MIG250LCD Welder w/ accessories & single cylinder undercarriage	115-230V/1/50/60	40-250A MIG 20-250A Stick 5-250A TIG	115V- 120A @ 60% 230V- 250A @ 60% 230V-194A @ 100%	MIG 27.7A 115V,38.2A 230V Stick 34.3A 115V,43.2A 230V TIG DC 20.5A 115V,28.9A 230V	58V	34.5x25x34.1	96.1	54.1
L13011	MIG250LCD Welder w/ accessories & dual cylinder undercarriage	115-230V/1/50/60	40-250A MIG 20-250A Stick 5-250A TIG	115V- 120A @ 60% 230V- 250A @ 60% 230V-194A @ 100%	MIG 27.7A 115V,38.2A 230V Stick 34.3A 115V,43.2A 230V TIG DC 20.5A 115V,28.9A 230V	58V	34.5x25x34.1	96.1	64.1



L13010

Features

- Synergic and Manual MIG Modes
- Metal dual drive roll system
- Dual gas input connections
- DC Stick Arc Force and Hot Start controls w/ VRD
- DC TIG HF start w/ pulse; remote amp control ready
- Spool gun ready
- Single or dual cylinder undercarriage option
- Spool sizes up to a maximum of 12 inch
- Dual cable hooks for easy storage of leads and guns
- 3-year power source warranty
- Digital Amperage control provides accurate control of output. Full color LCD interface for easy setup and adjustment.
- Solid welding wire diameters from .023 to .045 and Flux Cored .035 to .045

What's Included -

L13010 Machine w/ single cylinder undercarriage
L13011 Machine w/ dual cylinder undercarriage

- MIG250LCD Welder
- MIG Gun NT4 400A 15ft
- Electrode Holder 300A with 15' Cable and 35-50 dinse connector
- Ground Clamp 300A with 15' Cable and 35-50 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L13012 Single Cylinder Undercarriage only
- L13013 Dual Cylinder Undercarriage only
- L23058 Spool Gun 25ft 300A
- L22002 Foot Pedal amperage Control Weldpro
- L22026 Foot Pedal amperage Control SSC
- L25010 Hand amperage Control Weldpro
- L22038 TIG Torch CK17 LLCK1712RSFSL35
- L22027 TIG Torch CK26 LTL2625RSFSL35