

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I1eff)	Max Open Circuit Voltage (U0)	Dimensions (in)	Net Weight (lb) machine only
L13008	OMNI210 CK17 torch SSC Amp Control MIG/Stick/AC/DC TIG 5-200A 115/230V	115-230V/1/50/60	5-120A 115V 5-200A 230V	115V MIG 120A@30% Stick 120A@20% TIG 120A@50%	230V MIG 200A@30% Stick 200A@30% TIG 200A@50%	21.7A Stick 115V 23.6A Stick 230V	65V	21.1x10.4x18.4	50.5



L13008

Features

- AC/DC TIG, DC MIG/FCAW and Stick
- Spool gun ready (sold separately)
- Multi-function data display and digital controls with simple menu for ease of setup and adjustment
- 200 amp maximum welding current across all processes allows for welding of a wide range of materials and thicknesses
- AC TIG features high frequency start with balance, frequency, and full pulse controls, as well as square and sine wave shape options
- DC TIG features high frequency or lift-arc starting, with full pulse controls
- User adjustable MIG inductance for increased puddle control; VRD, hot start, and arc force adjustments for better stick welding
- High temp and overload protection with indicator lights
- Dual voltage 115/230V
- Separate dedicated gas inputs for TIG and MIG
- MIG wire spool capacity up to 12 lbs, (4" or 8")

What's Included -

L13008 OMNI210 CK17 torch MIG/Stick/AC/DC TIG 5-200A

- MIG torch: 10ft NT1 MIG torch
- TIG torch: 12ft CK 17-12-RSF Flex head TIG torch
- Trigger button for TIG torch
- Torch cable protection cover
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 300A with 10' Cable and 35-50 dinse connector
- Flow Meter
- Gas Hose
- Power adapter
- Drive rolls; knurled & v groove
- AK-3 accessory kit
- SSC amperage control foot pedal

Optional Accessories

- L23048 Spool Gun 15ft 150A
- L25007 Welding Cart Reg
- L25008 HD Welding Cart
- L25010 Hand amperage control Weldpro