

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
	TIGACDC200GD Stick/Tig Welder 15-200A 115/230V	115-230V/1/50/60	5-200A	115V 120A@40% Stick 120A@40% TIG	230V 180A@40% Stick 200A@40% TIG	28A Stick 16.7 TIG 115V 23.1A Stick 16.9 TIG 230V	59V	17.6x7.9x16.1	32.6



L12008

Features

- AC/DC TIG and Stick functions
- User friendly digital menu for easy setup and adjustment
- High frequency start and full pulse controls in both AC and DC TIG modes
- AC TIG balance and frequency adjustment
- TIG pre-flow, post flow, start/end amps, upslope and downslope adjustment
- 2T/4T option with included trigger button
- 5-200A TIG and 20-180A Stick output allows for welding of a wide variety of materials and thicknesses
- High temp and overload protection with indicator

TIG200ACDC Packages-

- L12000 TIG200ACDCGD Ergo17 torch AC/DC TIG 5-200A 115/230V
- L12003-1 TIG200ACDCGD CK17 Superflex torch AC/DC TIG 5-200A 115/230V
- L12008 TIG200ACDCGD KT26 torch AC/DC TIG 5-200A 115/230V

What's Included

- TIG torch
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 300A with 10' Cable and 35-50 dinse connector
- Trigger button for TIG torch
- Torch protection cover
- Flow Meter
- Gas Hose
- Power adapter
- Foot Pedal

Optional Accessories

- L25007 Welding Cart Reg
- L22026 Foot Pedal amperage Control SSC 5 pin
- L22027 CK26 200 amp Trim-line Air Cooler Torch
- L22028 CK 20-25SF FX SLWHAT without the Adapters
- L22004 TIG Torch CK17FX TIG
- L12005 Supercool W300 dual voltage water cooler 115/230V
- L25010 Hand amperage control Weldpro
- L25008 Welding Cart HD
- L22002 Foot Pedal amperage Control Weldpro
- L22039 TIG Torch KT26 Air Cooled Torch