



WELDING & CUTTING EQUIPMENT
www.weldpro.com

Company Profile

Lin Long Company (USA) is a comprehensive enterprise integrating marketing, R & D, sales and service. It was established in October 2016 and belongs to the Zhejiang Linlong Welding Equipment Co., Ltd. with a registered capital of USD 500,000.00. The company consists of: welding equipment, welding accessories, hardware tools, power integrated circuits and other products. The company' s products have passed CE certification, CETLus certification, TUV GS certification, TUV certification, S certification, VDE certification and other related certifications.

The parent company, Zhejiang Linlong Welding Equipment Company Ltd. has over 15 years experience in the welding equipment field and it has the advantages of a global marketing network, worldwide logistics and distribution expertise, 24/7 customer support and provides other benefits related to its global integration. The company' s comprehensive economic strength continues to enhance its ability of sustained growth and rapid product development.

At present, the company manufactures products under a number of brands for the OEM markets and owns a broad range of intellectual property rights. The company is positioned to offer "the most reasonable prices, the most perfect service, and provide the best products". The company' s mission is "to create opportunities for its employees, to create value for its customers, and to be responsible global citizen".

Zhejiang Linlong Welding Equipment Co. Ltd (Taizhou Shuanglong Electric Co.,Ltd), located in the southeast coast of Zhejiang Wenling, covering an area of 14000 square meters was founded in 1993. The company is a welding equipment research and development, production, sales and service, joint-stock cooperative enterprise all in one.



LINLONG WELDING

ICONS - ICONE

	Single phase		Three phase		Portable		Kit available		Accessories included
	Gas		No gas		WIRE SPEED Wire speed regulator		Thermostatic control		Inverter
	Fast/slow changing		ARC FORCE Arc force device		Wheel kit		High frequency start		Max. wire spool weight 5kg Max. wire size 1.0mm
	Welding time		2 gauges gas reduce		Lifting hooks		Unit applies Air compressor		Pilot arc starting
	DC Direct current		AC Alternate current		AC DC Direct and alternate current		Unit supplies Pulse		Current display
	IGBT		MOSFET		CPU		Constant current		Constant voltage
	TIG		MMA		MIG		HF TIG		Arc striking with contact
	CUT		Air carbon arc gouging		Pulse background		Pulse peak		Hot start
	Slope (increasing)		Slope (decreasing)		Variable inductance		Wire feed drive		Workpiece connection
	Remote control		60 Hz Frequency		Unit supplies Measurement Instruments (Digital)		Over current protection		Fan
	2T/4T								

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I _{1eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L11004	ARC121i DC Stick/Tig Welder 10-120 amps 115V	115V/1/50/60	10-120A	90A@100% Stick 90A@100% TIG	24.3A Stick 14.5A TIG	67V	8.5x7x5.5	5.5
SP2007	ARC121i TIG package w/9fv-6-2 dinse10-25, flow meter	115V/1/50/60	10-120A	90A@100% Stick 90A@100% TIG	24.3A Stick 14.5A TIG	67V	8.5x7x5.5	5.5
SP2006	ARC121i TIG package w/17V-12-2 dinse 10-25, flow meter	115V/1/50/60	10-120A	90A@100% Stick 90A@100% TIG	24.3A Stick 14.5A TIG	67V	8.5x7x5.5	5.5



SP2007

Features

- EXTREME PORTABILITY
- Less than 6 pounds
- Lift TIG DC
- DC Stick
- 2 year power source warranty
- Digital Amperage control provides accurate control of output.
- Lift Arc TIG provides a smooth, crisp arc and reduced Tungsten contamination.

What's Included - L11004 machine only

- ARC121i welder
- Electrode Holder 200A with 10' Cable and 10-25 dinse connector
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115V 20/30A
- Shoulder Strap

What's Included - SP2007 & SP2006 machine with TIG package

- ARC121i welder
- Electrode Holder 200A with 10' Cable and 10-25 dinse connector
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115V 20/30A
- Shoulder Strap
- TIG Torch 9FV-6-2 dinse 10-25 w/SP2007
- TIG Torch 17V-12-2 dinse 10-25 w/ SP2006
- Flow meter

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I1eff)	Max Open Circuit Voltage (U0)	Dimensions (in)	Net Weight (lb) machine only
L11008	StickPro 160 DC Stick/Tig Welder 20-160A 110-220V	110/220V/1/50/60	20-120A 110V 20-160A 220V	120A@30% Stick/TIG 110V 160A@30% Stick/TIG 220V	46.3A Stick 27.6A TIG 110V 32.9A Stick 20.4A TIG 220V	71V	12.8x5x8.3	9.3
L11009	StickPro 200 DC Stick/Tig Welder 20-200A 110-220V	110/220V/1/50/60	20-120A 110V 20-200A 220V	120A@30% Stick/TIG 110V 200A@30% Stick/TIG 220V	46.3A Stick 27.6A TIG 110V 43.6A Stick 28A TIG 220V	71V	12.8x5x8.3	9.9



L11008
L11009

Features

- Portable
- Less than 12 pounds
- Digital Amperage control provides accurate control of output.
- DC Stick
- 6010 cellulose rod capability built in circuit board.
- Lift TIG DC
- Remote amperage control ready
- Lift Arc TIG provides a smooth, crisp arc and reduced tungsten contamination.
- 3 year power source warranty

What's Included -

L11008 StickPro 160 machine
L11009 StickPro 200 machine

- StickPro 160 welder / StickPro 200 welder
- Electrode Holder 200A with 10' Cable and 10-25 dinse connector
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115/230V

Optional Accessories

- L22040 TIG Torch 9FV-6-2 dinse10-25
- L22020 TIG Torch 17V-12-2 dinse10-25
- L22003 Flow meter
- L22002 Foot Pedal amperage control
- L25010 Rotary Hand amperage control

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I _{1eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L13002	MIG155Gsv MIG/Stick 30-155A 115/230V	115/230V/1/50/60	30-155A MIG 30-140A Stick	115V MIG 75A@30% Stick 60A@30% 230V MIG 155A@30% Stick 140A@30%	20A 115V 30A 230V	59V	15x6.7x13.6	21.2



L13002

Features

- MIG and Stick modes
- DC TIG capable
- MIG gas input connection
- Spool sizes 2 lb
- 3-year power source warranty
- Light weight and portable design

What's Included -

L13002 MIG155Gsv MIG/Stick 30-155A 115/230V

- MIG155Gsv Welder
- MIG Gun 150A 7ft
- Electrode Holder 200A with 10' Cable and 10-25 dinse connector
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L25007 Welding Cart Reg
- L22020 TIG Torch 17 V-12 150A with gas valve, hose and 10-25 dinse

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I1eff)	Max Open Circuit Voltage (U0)	Dimensions (in)	Net Weight (lb) machine only
L13006	MIG155GD MIG/Stick 30-155A 115/230V	115/230V/1/50/60	30-155A MIG 30-140A Stick	115V MIG 75A@30% Stick 60A@30% 230V MIG 155A@30% Stick 140A@30%	20A 115V 30A 230V	59V	15x6.7x13.6	21.2



L13006

Features

- MIG and Stick modes
- DC TIG capable
- MIG gas input connection
- Spool sizes 2 lb
- 3-year power source warranty
- Light weight and portable design
- Removable MIG gun
- Spool gun ready

What's Included -

L13006 MIG155GD MIG/Stick 30-155A 115/230V

- MIG155GD Welder
- MIG Gun 150A 10ft
- Electrode Holder 200A with 10' Cable and 10-25 dinse connector
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L25007 Welding Cart Reg
- L22020 TIG Torch 17 V-12 150A with gas valve, hose and 10-25 dinse
- L23048 Spool gun 15ft 150A

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L13014	MIG160i 30-160A 115/230V	115-230V/1/50/60	30-160A MIG	115V MIG 120A@30%	230V MIG 160A@30%	24.3A 115V 23A 230V	65V	17.7x8.6x13.9	25.5



L13014

Features

- Dual voltage input 115V and 230V
- Metal drive roll system
- MIG gas input connection
- Easy to use with basic setup
- Infinitely adjustable voltage and wire feed speed
- Spool gun ready
- Spool sizes 11 and 2 lb
- 3-year power source warranty

What's Included -

L13014 MIG160i MIG welder 30-160A 115/230V

- MIG160i Welder
- MIG Gun NT1 150A 10ft
- Ground Clamp 200A with 10' Cable and 35-50 disne connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L23048 Spool Gun 15ft 150A
- L25007 Welding Cart Reg

MIG200i

• Input Power 115-230V/1/50/60

- DC Stick (SMAW)
- DC TIG (GTAW)
- MIG (GMAW)
- Flux Cored (FCAW)
- CV/CC-DC

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L13015	MIG200i MIG/Stick/TIG 10-200A 115/230V	115-230V/1/50/60	30-200A MIG 20-200A Stick 10-200A TIG	115V MIG 120A@30% Stick 120A@30% TIG 120A@30%	230V MIG 200A@30% Stick 200A@30% TIG 200A@30%	20A 115V 40A 230V	60V	17.7x8.6x13.9	27.5



L13015

Features

- 3 in 1 function MIG, Stick and Lift TIG DC
- Digital Amperage display provides accurate control of output.
- Metal drive roll system
- MIG gas input connection
- Spool sizes 11 and 2 lb
- Spool gun ready
- 3-year power source warranty.

What's Included -

L13015 MIG200i MIG/Stick/TIG 30-200A 115/230V

- MIG200i Welder
- MIG Gun NT1 150A 10ft
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 200A with 10' Cable and 35-50 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L23048 Spool Gun 15ft 150A
- L25007 Welding Cart Reg
- L22020 17V12-2 TIG torch

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L13007	MIG210LCD	115-230V/1/50/60	40-200A MIG 20-200A Stick 20-200A TIG	115V MIG 120A@30% Stick 120A@30% TIG 120A@30%	230V MIG 200A@30% Stick 200A@30% TIG 200A@30%	24.3A 115V 23A 230V	65V	17.4x8.3x14.6	30



L13007

Features

- Full color LCD display with simple to set digital controls.
- Synergic and Manual MIG Modes
- Metal drive roll system
- MIG gas input connection
- DC Stick Arc Force and Hot Start controls w/ VRD
- DC TIG lift start
- Spool gun ready
- 3 in 1 function MIG, Stick and Lift TIG DC
- Spool sizes 11lb and 2 lb
- MIG run-in speed, inductance, and adjustable spot timer.
- 3-year power source warranty

What's Included -

L13007 MIG210LCD MIG/Stick/TIG 30-210A 115/230V

- MIG210LCD Welder
- MIG Gun NT1 150A 10ft
- TIG Torch 17V 12'
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 200A with 10' Cable and 35-50 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L23048 Spool Gun 15ft 150A
- L25007 Welding Cart Reg

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only	Net Weight (lb) cylinder undercarriage only
L13010	MIG250LCD Welder w/ accessories & single cylinder undercarriage	115-230V/1/50/60	40-250A MIG 20-250A Stick 5-250A TIG	115V- 120A @ 60% 230V- 250A @ 60% 230V-194A @ 100%	MIG 27.7A 115V,38.2A 230V Stick 34.3A 115V,43.2A 230V TIG DC 20.5A 115V,28.9A 230V	58V	34.5x25x34.1	96.1	54.1
L13011	MIG250LCD Welder w/ accessories & dual cylinder undercarriage	115-230V/1/50/60	40-250A MIG 20-250A Stick 5-250A TIG	115V- 120A @ 60% 230V- 250A @ 60% 230V-194A @ 100%	MIG 27.7A 115V,38.2A 230V Stick 34.3A 115V,43.2A 230V TIG DC 20.5A 115V,28.9A 230V	58V	34.5x25x34.1	96.1	64.1



L13010

Features

- Synergic and Manual MIG Modes
- Metal dual drive roll system
- Dual gas input connections
- DC Stick Arc Force and Hot Start controls w/ VRD
- DC TIG HF start w/ pulse; remote amp control ready
- Spool gun ready
- Single or dual cylinder undercarriage option
- Spool sizes up to a maximum of 12 inch
- Dual cable hooks for easy storage of leads and guns
- 3-year power source warranty
- Digital Amperage control provides accurate control of output. Full color LCD interface for easy setup and adjustment.
- Solid welding wire diameters from .023 to .045 and Flux Cored .035 to .045

What's Included -

L13010 Machine w/ single cylinder undercarriage
L13011 Machine w/ dual cylinder undercarriage

- MIG250LCD Welder
- MIG Gun NT4 400A 15ft
- Electrode Holder 300A with 15' Cable and 35-50 dinse connector
- Ground Clamp 300A with 15' Cable and 35-50 dinse connector
- Power Adapter 115/230V
- Flow Meter
- Gas Hose

Optional Accessories

- L13012 Single Cylinder Undercarriage only
- L13013 Dual Cylinder Undercarriage only
- L23058 Spool Gun 25ft 300A
- L22002 Foot Pedal amperage Control Weldpro
- L22026 Foot Pedal amperage Control SSC
- L25010 Hand amperage Control Weldpro
- L22038 TIG Torch CK17 LLCK1712RSFSL35
- L22027 TIG Torch CK26 LTL2625RSFSL35

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L13008	OMNI210 CK17 torch SSC Amp Control MIG/Stick/AC/DC TIG 5-200A 115/230V	115-230V/1/50/60	5-120A 115V 5-200A 230V	115V MIG 120A@30% Stick 120A@20% TIG 120A@50%	230V MIG 200A@30% Stick 200A@30% TIG 200A@50%	21.7A Stick 115V 23.6A Stick 230V	65V	21.1x10.4x18.4	50.5



L13008

Features

- AC/DC TIG, DC MIG/FCAW and Stick
- Spool gun ready (sold separately)
- Multi-function data display and digital controls with simple menu for ease of setup and adjustment
- 200 amp maximum welding current across all processes allows for welding of a wide range of materials and thicknesses
- AC TIG features high frequency start with balance, frequency, and full pulse controls, as well as square and sine wave shape options
- DC TIG features high frequency or lift-arc starting, with full pulse controls
- User adjustable MIG inductance for increased puddle control; VRD, hot start, and arc force adjustments for better stick welding
- High temp and overload protection with indicator lights
- Dual voltage 115/230V
- Separate dedicated gas inputs for TIG and MIG
- MIG wire spool capacity up to 12 lbs, (4" or 8")

What's Included -

L13008 OMNI210 CK17 torch MIG/Stick/AC/DC TIG 5-200A

- MIG torch: 10ft NT1 MIG torch
- TIG torch: 12ft CK 17-12-RSF Flex head TIG torch
- Trigger button for TIG torch
- Torch cable protection cover
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 300A with 10' Cable and 35-50 dinse connector
- Flow Meter
- Gas Hose
- Power adapter
- Drive rolls; knurled & v groove
- AK-3 accessory kit
- SSC amperage control foot pedal

Optional Accessories

- L23048 Spool Gun 15ft 150A
- L25007 Welding Cart Reg
- L22027 CK26 200 amp Trimline air cooled torch 25ft
- L25010 Hand amperage control Weldpro

Part Number	Model	Length	Amperage Rated @ 60% Duty Cycle	Cooling	Wire Size Range	Net Weight (lb)
L23048	Spool Gun 150A 15ft	15ft	150A	Air	.030" to .035"	7.4
L23075	Spool Gun 300A 15ft	15ft	300A	Air	.030" to 3/64"	11.1
L23058	Spool Gun 300A 25ft	25ft	300A	Air	.030" to 3/64"	14.6

L23048



L23075 or L23058



Features

Weldpro spool guns are designed for plug-and-play use with Weldpro MIG welding machines, with no adapters required. They are designed to be lightweight and comfortable for use in all positions, with a fully enclosed wire spool to keep wire clean. All spool gun models use industry standard consumables.

Part Numbers

- L23048 Spool Gun 150 A 15 ft
- L23075 Spool Gun 300 A 15 ft
- L23058 Spool Gun 300 A 25 ft

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L12003-1	TIGACDC200GD Stick/Tig Welder 15-200A 115/230V	115-230V/1/50/60	5-200A	115V 120A@40% Stick 120A@40% TIG	230V 180A@40% Stick 200A@40% TIG	28A Stick 16.7 TIG 115V 23.1A Stick 16.9 TIG 230V	59V	17.6x7.9x16.1	32.6



L12003-1

Features

- AC/DC TIG and Stick functions
- User friendly digital menu for easy setup and adjustment
- High frequency start and full pulse controls in both AC and DC TIG modes
- AC TIG balance and frequency adjustment
- TIG pre-flow, post flow, start/end amps, upslope and downslope adjustment
- 2T/4T option with included trigger button
- 5-200A TIG and 20-180A Stick output allows for welding of a wide variety of materials and thicknesses
- High temp and overload protection with indicator

TIG200ACDC Packages-

- L12003-1 TIG200ACDCGD CK17 Superflex torch AC/DC TIG 5-200A 115/230V

What's Included

- TIG torch
- Electrode Holder 200A with 10' Cable and 35-50 dinse connector
- Ground Clamp 300A with 10' Cable and 35-50 dinse connector
- Trigger button for TIG torch
- Torch protection cover
- Flow Meter
- Gas Hose
- Power adapter
- Foot Pedal amperage control Weldpro 5pin

Optional Accessories

- L25007 Welding Cart Reg
- L22026 Foot Pedal amperage Control SSC 5 pin
- L22027 CK26 200 amp Trim-line air cooled torch 25ft
- L22028 CK 20-25SF FX SLWHAT 250A water cooled 25ft
- L22004 TIG Torch CK17FX 150 amp air cooled 12.5ft
- L12005 Supercool W300 dual voltage water cooler 115/230V
- L25010 Hand amperage control Weldpro
- L25008 Welding Cart HD

Part Number	Model	Input Power	Welding Amperage Range	Rated Output		Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
See Below	TIGACDC250GD Stick/Tig Welder 15-200A 115/230V	115/230V/1/50/60	5-250A	115V 120A@40% Stick 120A@40% TIG	230V 220A@30% Stick 250A@30% TIG	25.4A TIG 115V 37.2 TIG 230V	59V	20.3x9.7x22.6	79.4



L12004-1

Features

- AC/DC TIG and Stick functions
- User friendly digital menu for easy setup and adjustment
- High frequency start and full pulse controls in both AC and DC TIG modes
- AC TIG balance and frequency adjustment
- TIG pre-flow, post flow, start/end amps, upslope and downslope adjustment
- 2T/4T option with included trigger button
- 5-250A TIG and 20-220A Stick output allows for welding of a wide variety of materials and thicknesses
- High temp and overload protection with indicator

TIG250ACDC Packages-

- L12004-1 TIG250 Digital 250 Amp AC/DC TIG Welder with Pulse w/CKTL26 Gas-Cooled Torch, SSC Amp Control
- L12006-1 TIG250 Digital 250 Amp AC/DC TIG Welder with Pulse w/ERGOTIG20 Water-cooled TORCH, SSC Amp Control
- L12007-1 TIG250 Digital 250 Amp AC/DC TIG Welder with Pulse w/CK20 Water-Cooled Torch, SSC Amp Control
- SP2004 TIG250 Digital 250 Amp AC/DC TIG Welder with Pulse w/ERGOTIG20 Water-cooled TORCH, W300 watercooler, SSC Amp control & HD CART
- SP2005 TIG250 Digital 250 Amp AC/DC TIG Welder with Pulse w/CK20 Water-Cooled Torch, W300 watercooler, SSC Amp Control & HD CART

What's Included

- Trigger button for TIG torch
- Torch protection cover
- Electrode holder 10ft 200A 35-50 dinse connector
- Ground clamp 10ft 300A 35-50 dinse connector
- SSC Foot AMP control
- Flow Meter
- Gas Hose
- Power adapter
- TIG Torch as listed in package

Optional Accessories

- L25007 Welding Cart Reg
- L25008 Welding Cart HD
- L22002 Foot Pedal amperage Control Weldpro Style 5 pin
- L22026 Foot Pedal amperage Control SSC 5 pin
- L22027 CK26 200 amp Trimline air cooled torch 25ft
- L22028 CK 20-255F FX SLWHAT 250 amp water cooled 25ft
- L22004 TIG Torch CK17FX 150 amp air cooled 12.5ft
- L22034 TIG Torch TIG20 250 amp water cooled torch 25ft
- L12005 Supercool W300 dual voltage water cooler 115/230V
- L25010 Hand amperage control Weldpro



L22002



L22053



L22026



L25010

Features

L22002

Weldpro Foot Pedal; 5-pin

- Heavy-duty steel, rocker style construction
- Full amperage and contactor control
- 15 foot cable with 5-pin remote plug

L22026

SSC Controls Foot Pedal; 5-pin

- Designed and manufactured in the USA
- Heavy-duty steel, rocker style construction
- Wide base, low profile, and non-slip traction pad provide secure footing and stability
- Precise current adjustment with industrial potentiometer resolution
- Improved low-current welding with patented design
- 25 foot cable with 5-pin remote plug
- Balanced spring force for responsive and comfortable feel
- Certified to CSA and UL standards

L22053

Weldpro Wireless Foot Pedal; 5-pin

- Steel construction, rocker style pedal with traction pad and rubber foot pads
- Remote amperage and contactor control with 80 foot operating range
- 120V powered receiver with 5-pin remote plug
- Wireless design eliminates cable snags and entanglements

L25010

Weldpro Rotary Hand Amp Control; 5-pin

- Hand amperage and contactor control with north/south rotary-motion dial
- Attaches to TIG torch handle with cable ties
- 25 foot cable with 5-pin remote plug

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I1eff)	Max Open Circuit Voltage (U0)	Dimensions (in)	Net Weight (lb) machine only
L14007	CUT40HF Plasma w/HF 14-40A 115/230V	115/230V/1/50/60	15-30A 115V 15-40A 230V	115V 30A@60% 230V 40A@60%	31.8A 115V 22.2 230V	325V	18.5x6.7x12.4	22
L14008	CUT60HF Plasma w/HF 14-60A 115/230V	115/230V/1/50/60	20-30A 115V 20-60A 230V	115V 30A@60% 230V 60A@60%	41.1A 115V 46.4 230V	266V	20.3x7.9x15.2	33.5



L14007 and L14008

Features

- Input 115V or 230V
- Easily cuts steel up to 1/2" 40A and 3/4" 60A
- 20' torch cable; 10' ground cable with clamp
- Common consumables, lightweight and portable
- Digital amperage control
- Air pressure adjustment and gauge on panel
- 3-year warranty Power Source
- High Frequency Start

What's Included -

L14007 Cut40HF Plasma Machine
L14008 Cut60HF Plasma Machine

- 20' Cutting Torch
- Ground Clamp 200A with 10' Cable and 10-25 dinse connector
- Power Adapter 115/230V

Cutting Capacity

- 40A – 1/2"
 - 60A – 3/4"
 - Material – stainless steel, aluminum, copper, cast iron, carbon steel
- Cutting thickness capacities vary with thermal conductivity of metals being cut

Part Number	Model	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Output (I _{eff})	Max Open Circuit Voltage (U ₀)	Dimensions (in)	Net Weight (lb) machine only
L14003	CUT40NH Plasma noHF 14-40A 115/230V	115-230V/1/50/60	15-30A 115V 15-40A 230V	115V 30A@60% 230V 40A@60%	31.8A 115V 22.2 230V	266V	16.9x6.7x12.4	20.5
L14005	CUT60NH Plasma noHF 14-60A 115/230V	115-230V/1/50/60	20-30A 115V 20-60A 230V	115V 30A@60% 230V 60A@60%	41.1A 115V 46.4 230V	266V	20.3x7.9x15.2	32.6



L14003 and L14005

Features

- Input 115V or 230V
- Easily cuts steel up to 1/2" 40A and 3/4" 60A
- 20' torch cable; 10' ground cable with clamp
- Common consumables, lightweight and portable
- Digital amperage control
- Air pressure adjustment and gauge on panel
- 3-year warranty Power Source
- Non High Frequency start

What's Included -

L14003 Cut40NH Plasma Machine Pkg
L14005 Cut60NH Plasma Machine Pkg

- 20' Cutting Torch
- Ground Clamp 200A with 10' Cable and 10-25 disne connector
- Power Adapter 115/230V

Cutting Capacity

- 40A – 1/2"
 - 60A – 3/4"
 - Material – stainless steel, aluminum, copper, cast iron, carbon steel
- Cutting thickness capacities vary with thermal conductivity of metals being cut

Part Number	Description	Input Power	Cooling capacity	Flow rating	Tank capacity	Dimensions (in)	Net weight (lb.)
L12006	Supercool W300 dual voltage water cooler 115/230V	115/230V/ 1/50/60	1L/Min	2.5L/Min	1.7 gal	25x9.5x9.7	31

Supercool W300

The Weldpro Supercool W300 (L12006) is a powerful, dual voltage (115/230V) water cooler designed for use with the Weldpro TIGACDC250GD. It can also be used with all other Weldpro TIG welders and any other brand/model machine requiring less than or equal to the W300's cooling capacity. A 1.7 gallon tank and 260-watt motor provide 8.5 LPM flow rate. The power switch is located in the front, along with quick-fit water connections and both a drain and priming plug.



L12006

Welding Cart Specifications

	Standard	Heavy Duty
Assembled Height (in)	32	44.5
Assembled Width (in)	18	18
Assembled Length (in)	42	33
Wheelbase (in)	28	28
Top Shelf Dimensions (in)	21x13	25.5x12
Middle Shelf Dimensions (in)	20x13	NA
Bottom Shelf Dimensions (in)	21x13.5	25.5x12
Height; Bottom Shelf (in)	14	11
Height; Middle Shelf (in)	10	NA
Weight Capacity (lbs)	350	400
Net Weight (lb.)	41	57

Heavy Duty Welding Cart

The Weldpro HD welder cart (L25008) is designed specifically for use with the Weldpro TIGACDC250GD welder and Weldpro W300 Supercool water cooler. Heavy duty front casters and molded rear wheels make it a stable and easy to move cart, and the rear tray will hold a single 300CF gas cylinder.



L25008

Standard Welding Cart

The Weldpro standard welder cart (L25007) is designed for use with a wide range of welding and plasma cutting machines. The large top shelf will accommodate any Weldpro unit below the 250A class machines. The middle shelf is designed to hold filler wire, tools, and other accessories, and the bottom shelf can be used for smaller machines or larger accessories. Use the two side hooks for cable and gun storage. A front mounted handle, heavy duty front casters and molded rear wheels make it a stable and easy to move cart.














L25007












Picture	Part Number	Description	Unit Of Measure	Class	Arc121i	MMA160 MMA200	StickPro 160 StickPro 200
	L21002	Electrode Holder 200A with 10' Cable and 10-25 connector dinse	each (1)	A	√	√	√
	L21004	Power Adaptor 115/230V	each (1)	A		√	√
	L21012	Connector Dinse 10-25 Male End	each (1)	A	√	√	√
	L21013	Connector Dinse 10-25 Female End	each (1)	A	√	√	√
	L21014	Power Adaptor 115 20/30A	each (1)	A	√	√	√
	L21015	Shoulder Strap 121	each (1)	A	√		
	L21003	Ground Clamp 200A with 10' Cable and 10-25 connector dinse	each (1)	A	√	√	√
	L23008	Electrode Holder 200A	each (1)	A	√	√	√
	L23009	Ground Clamp Steel 200A	each (1)	A	√	√	√
	L22003	Flow Meter CGA 580	each (1)	A	√	√	√
	L25000	Flow Gauge CGA 580	each (1)	A	√	√	√
	L22020	TIG Torch 17 V-12 150A with gas valve, hose and 10-25 connector dinse	each (1)	A	√	√	√
	L22010	Cup Alumina 10N08 #4 S17,18,26	pkg (5)	C	√	√	√
	L22011	Cup Alumina 10N09 #5 S17,18,26	pkg (5)	C	√	√	√
	L22012	Cup Alumina 10N48 #6 S17,18,26	pkg (5)	C	√	√	√
	L22045	Cup Alumina 10N47 #7 S17,18,26	pkg (5)	C	√	√	√
	L22044	Cup Alumina 10N46 #8 S17,18,26	pkg (5)	C	√	√	√















Picture	Part Number	Description	Unit Of Measure	Class	Arc121i	MMA160 MMA200	StickPro 160 StickPro 200
	L22013	Collet 10N23 1/16 S17,18,26	pkg (5)	C	√	√	√
	L22015	Collet 10N24 3/32 S17,18,26	pkg (5)	C	√	√	√
	L22041	Collet 10N25 1/8 S 17,18,26	pkg (5)	C	√	√	√
	L22043	Collet Body 10N31 1/16 S17,18,26	pkg (5)	C	√	√	√
	L22016	Collet Body 10N32 3/32 S17,18,26	pkg (5)	C	√	√	√
	L22042	Collet Body 10N28 1/8 S17,18,26	pkg (5)	C	√	√	√
	L22017	Backcap Long 57Y02 S17,18,26	each (1)	C	√	√	√
	L22018	Backcap Short 57Y04 S17,18,26	each (1)	C	√	√	√
	L22031	Kit Gas Lense S17,18,26	each (1)	A	√	√	√
	L22025	Cover TIG torch 17 style 12'	each (1)	A	√	√	√
	L22040	TIG Torch 9 FV-6 125A with gas valve, hose and 10-25 connector disne	each (1)	A	√	√	√
	L22046	Cup Alumina 13N09 #5 S9,20	pkg (5)	C	√	√	√
	L22047	Collet 13N22 1/16 S9,20	pkg (5)	C	√	√	√
	L22048	Collet 13N23 3/32 S9,20	pkg (5)	C	√	√	√
	L22049	Collet Body 13N27 1/16 S9,20	pkg (5)	C	√	√	√
	L22050	Collet Body 13N28 3/32 S9,20	pkg (5)	C	√	√	√
	L22032	Kit Gas Lense S9,20	each (1)	A	√	√	√
	L22051	Backcap Long 41V24 S9,20	each (1)	C	√	√	√
	L22052	Backcap Short 41V33 S9,20	each (1)	C	√	√	√
	L25010	Weldpro Rotary Hand Amperage Control 5 pin 25'	each (1)	A			√
	L22026	SSC Foot Pedal Amperage Control 25' 5-pin	each (1)	A			√










Picture	Part Number	Description	Unit Of Measure	Class	MIG250LCD	Omni210	MIG160 MIG200 MIG210LCD	MIG155GD MIG155Gsv
	L23004	Drive Roll V-Groove .030/.040	each (1)	A		√	√	
	L23005	Drive Roll V-Groove .023/.030/.035	each (1)	A		√	√	
	L23006	Drive Roll K-Groove .030/.035	each (1)	A		√	√	
	L23010	Drive Roll K-Groove .030/.035	each (1)	A				√
	L23013	Contact Tip .023 (11-23)	pkg (5)	C		√	√	√
	L23014	Contact Tip .030 (11-30)	pkg (5)	C		√	√	√
	L23015	Contact Tip .035 (11-35)	pkg (5)	C		√	√	√
	L23016	Contact Tip .040 (11-40)	pkg (5)	C		√	√	√
	L23019	Steel Replacement Liner	each (1)	A		√	√	
	L23020	Teflon Replacement Liner	each (1)	A		√	√	*
	L23028	Thread On Nozzle, Chrome (21-50)	pkg (2)	C		√	√	√
	L23030	Drive Roll V-Groove .030/.035	each (1)	A				√
	L23032	NT1 MIG Torch, 180A, 10'	each (1)	A	√	√	√	
	L23033	Thread On Nozzle, Copper (21-50)	pkg (2)	C		√	√	√
	L23034	Gas Diffuser, RH Thread (#51)	pkg (2)	C		√	√	
	L23035	SB2 MIG Torch, 150A, 10'	each (1)	A				*
	L23038	Steel Replacement Liner	each (1)	A				*
	L23039	Steel Replacement Liner	each (1)	A				**
	L23040	Gas Diffuser, RH Thread (35-50)	pkg (2)	C				√
	L23047	MIG Torch O-Ring Set	pkg (2)	C	√	√	√	√
	L23051	MIG Gun NT4 15ft 400A	each (1)	A	√	√	√	
	L23059	Drive Roll Set V-Groove .025/.035	each (1)	A	√			
	L23060	Drive Roll Set V-Groove .035/.045	each (1)	A	√			
	L23061	Drive Roll Set K-Groove .035/.045	each (1)	A	√			

Picture	Part Number	Description	Unit Of Measure	Class	MIG250LCD	Omni210	MIG160 MIG200 MIG210LCD	MIG155GD MIG155Gsv
	L23064	Contact Tip .025 (14-25)	pkg (5)	C	√			
	L23065	Contact Tip .030 (14-30)	pkg (5)	C	√			
	L23066	Contact Tip .035 (14-35)	pkg (5)	C	√			
	L23067	Contact Tip .045 (14-45)	pkg (5)	C	√			
	L23068	Contact Tip 3/64 (14-364)	pkg (5)	C	√			
	L23069	Contact Tip 1/16 (14-116)	pkg (5)	C	√			
	L23070	Nozzle (24CT-62S)	pkg (2)	C	√			
	L23071	Diffuser, RH Thread (54A)	pkg (2)	C	√			
	L23072	Steel Liner (44-3545-15)	each (1)	A	√			
	L23073	Insulator (34CT)	pkg (2)	C	√			
	L23074	Spindle For Wire Spool Adapter Assembly	each (1)	A	√			
	L21002	Electrode Holder 200A with 10' Cable and 10-25 Dinse Connector	each (1)	A				√
	L21003	Ground Clamp 200A with 10' Cable and 10-25 Dinse Connector	each (1)	A				√
	L21004	Power Adaptor 115/230V	each (1)	A	√	√	√	√
	L21012	Connector Dinse 10-25 Male End	each (1)	A				√
	L21013	Connector Dinse 10-25 Female End	each (1)	A				√
	L22001	Gas Hose Inert 6ft	each (1)	A	√	√	√	√
	L22002	Foot Pedal Weldpro Style 5 pin	each (1)	A	√	√		
	L22003	Flow Meter CGA 580	each (1)	A	√	√	√	√
	L22019	TIG Trigger Button 14' 5-pin	each (1)	A	√	√		
	L22020	TIG Torch 17V 12.5' Valve Style with 10-25 Dinse Connector	each (1)	A				√
	L22026	Foot Pedal SSC Controls 5 pin	each (1)	A	√	√		
	L22027	CK26 Trimline TIG Torch 25'	each (1)	A	√	√		
	L22033	TIG Trigger Button 25' 5-pin	each (1)	A	√	√		

Picture	Part Number	Description	Unit Of Measure	Class	MIG250LCD	Omni210	MIG160 MIG200 MIG210LCD	MIG155GD MIG155Gsv
	L22035	TIG Torch 17V 12.5' Valve Style with 35-50 Dinse Connector	each (1)	A			√	
	L22038	TIG Torch CK17 12.5' with SL8-35 Dinse Connector	each (1)	A	√	√		
	L22040	TIG Torch 9FV 6' with 10-25 Dinse Connector	each (1)	A				√
	L22053	Weldpro Wireless Foot Pedal	each (1)	A	√	√		
	L23002	Electrode Holder 200A with 10' Cable and 35-50 Dinse Connector	each (1)	A	√	√	√	
	L23008	Electrode Holder 200A	each (1)	A	√	√	√	√
	L23009	Ground Clamp Steel 200A	each (1)	A	√	√	√	√
	L23031	Ground Clamp 200A with 10' Cable and 35-50 Dinse Connector	each (1)	A	√	√	√	
	L23048	Spool Gun 150A 15'	each (1)	M	√	√	√	*
	L23049	T-shape Ground Clamp Brass 200A	each (1)	A	√	√	√	√
	L23052	Ground Clamp 300A with 15ft Cable and 35-50 Dinse Connector	each (1)	A	√	√	√	
	L23053	Electrode Holder 300A with 15ft Cable and 35-50 Dinse Connector	each (1)	A	√	√	√	
	L23054	Connector Dinse 35-50 Male	each (1)	A	√	√	√	
	L23055	Connector Dinse 35-50 Female	each (1)	A	√	√	√	
	L23056	Ground Clamp Steel 500A	each (1)	A	√	√	√	√
	L23057	Electrode Holder 300A	each (1)	A	√	√	√	√
	L23058	Spool Gun 300A 25'	each (1)	M	√	√	√	
	L23075	Spool Gun 300A 15'	each (1)	M	√	√	√	
	L24001	Ground Clamp Steel 300A	each (1)	A	√	√	√	√
	L25000	Flow Gauge CGA 580	each (1)	A	√	√	√	√
	L25005	Ground Clamp Brass 300A	each (1)	A	√	√	√	√
	L25006	MIG 8" Wire Spool Adapter Assembly	each (1)	A		√	√	
	L25007	Welding Cart Standard	each (1)	A		√	√	√
	L25009	Machine Protection Cover	each (1)	A			√	
	L25010	Weldpro Remote Hand Amperage Control 5 pin	each (1)	A	√	√		

Picture	Part Number	Description	Unit Of Measure	Class	SG300A Spool Gun	SB8 Spool Gun
	L23078	Nozzle, Slip On (22-62)	pkg (2)	C	√	
	L23079	Insulator (#32)	pkg (2)	C	√	
	L23080	Diffuser, RH Thread (#52)	pkg (2)	C	√	
	L23013	Contact Tip .023 (11-23)	pkg (5)	C		√
	L23014	Contact Tip .030 (11-30)	pkg (5)	C		√
	L23015	Contact Tip .035 (11-35)	pkg (5)	C		√
	L23016	Contact Tip .040 (11-40)	pkg (5)	C		√
	L23028	Thread On Nozzle, Chrome (21-50)	pkg (2)	C		√
	L23033	Thread On Nozzle, Copper (21-50)	pkg (2)	C		√
	L23040	Gas Diffuser, RH Thread (35-50)	pkg (2)	C		√
	L23041	Drive Roll - Spool Gun	each (1)	A		√
	L23042	Replacement Liner - Spool Gun	each (1)	A		√
	L23047	MIG Torch O-Ring Set	pkg (2)	C	√	√
	L23062	Drive Roll Set Spool Gun .030/.035	each (1)	A	√	
	L23063	Drive Roll Set Spool Gun .045 to 3/64	each (1)	A	√	
	L23064	Contact Tip .025 (14-25)	pkg (5)	C	√	
	L23065	Contact Tip .030 (14-30)	pkg (5)	C	√	
	L23066	Contact Tip .035 (14-35)	pkg (5)	C	√	
	L23067	Contact Tip .045 (14-45)	pkg (5)	C	√	
	L23068	Contact Tip 3/64 (14-364)	pkg (5)	C	√	
	L23069	Contact Tip 1/16 (14-116)	pkg (5)	C	√	

Picture	Part Number	Description	Unit Of Measure	Class	Omni210	TIG200ACDC	TIG250ACDC
	L12005	Water Cooler W300 Supercool 115/230V	each (1)	M	√	*	√
	L21014	Power Adaptor 115 20/30A	each (1)	A	√	√	√
	L23008	Electrode Holder 200A	each (1)	A	√	√	√
	L23009	Ground Clamp Steel 200A	each (1)	A	√	√	√
	L24001	Ground Clamp Steel 300A	each (1)	A	√	√	√
	L22001	Gas Hose 55"	each (1)	A	√	√	√
	L22002	Weldpro Foot Pedal Amperage Control 5-pim 16'	each (1)	A	√	√	√
	L22003	Flow Meter Argon or Argon CO2 CGA 580	each (1)	A	√	√	√
	L22004	TIG Torch CK17FX 150A 12.5' M16 Connection	each (1)	A		**	
	L22000	TIG Torch Ergo17 150A 12.5' M16 Connection	each (1)	A		**	
	L22010	Cup Alumina 10N08 #4 S17,18,26	pkg (5)	C	√	√	√
	L22011	Cup Alumina 10N09 #5 S17,18,26	pkg (5)	C	√	√	√
	L22012	Cup Alumina 10N48 #6 S17,18,26	pkg (5)	C	√	√	√
	L22013	Collet 10N23 1/16 S17,18,26	pkg (5)	C	√	√	√
	L22015	Collet 10N24 3/32 S17,18,26	pkg (5)	C	√	√	√
	L22041	Collet 10N25 1/8 S 17,18,26	pkg (5)	C	√	√	√
	L22016	Collet Body 10N32 3/32 S17,18,26	pkg (5)	C	√	√	√
	L22042	Collet Body 10N28 1/8 S17,18,26	pkg (5)	C	√	√	√
	L22043	Collet Body 10N31 1/16 S17,18,26	pkg (5)	C	√	√	√
	L22017	Backcap Long 57Y02 S17,18,26	each (1)	C	√	√	√

Picture	Part Number	Description	Unit Of Measure	Class	Omni210	TIG200ACDC	TIG250ACDC
	L22018	Backcap Short 57Y04 S17,18,26	each (1)	C	√	√	√
	L22019	TIG Trigger Switch 14' 5-pin	each (1)	A	√	√	√
	L22025	Cover TIG Torch 12'	each (1)	A	√	√	√
	L22026	SSC Foot Pedal Amperage Control 25' 5-pin	each (1)	A	√	√	√
	L22027	TIG Torch CK26 Trimline Air Cooler 200A Dinse 35-50 LLTL2625RSFSL35	each (1)	A	√	*	√
	L22028	TIG Torch CK 20 Water Cooled 250A 25' Dinse 35-50 LLCK2025SFFSL35	each (1)	A	√	*	√
	L22029	Quick Connect Adapter Plug, Water, Male	each (1)	A	√	√	√
	L22030	Quick Connect Adapter Plug, Gas, Male	each (1)	A	√	***	√
	L22031	Kit Gas Lens S17,18,26	each (1)	A	√	√	√
	L22032	Kit Gas Lens S9,20	each (1)	A	√	√	√
	L22033	TIG Trigger Switch 25' 5-pin	each (1)	A	√	√	√
	L22034	TIG Torch Weldpro WP20 Water Cooled 250A 25' Dinse 35-50 LL2025SFFSL35	each (1)	A	√	*	√
	L22037	Cover TIG Torch 25'	each (1)	A	√	√	√
	L22038	TIG Torch CK17FX 150A 12.5' Dinse 30-50 Connector LLCK1712RSFSL35	each (1)	A	√	*	√
	L22039	TIG Torch Weldpro KT26 200A 12.5' M16 Connector	each (1)	A		**	
	L22044	Cup Alumina 10N46 #8 S17,18,26	pkg (5)	C	√	√	√
	L22045	Cup Alumina 10N47 #7 S17,18,26	pkg (5)	C	√	√	√
	L22046	Cup Alumina 13N09 #5 S9,20	pkg (5)	C	√	√	√
	L22047	Collet 13N22 1/16 S9,20	pkg (5)	C	√	√	√
	L22048	Collet 13N23 3/32 S9,20	pkg (5)	C	√	√	√

Picture	Part Number	Description	Unit Of. Measure	Class	Omni210	TIG200ACDC	TIG250ACDC
	L22049	Collet Body 13N27 1/16 S9,20	pkg (5)	C	√	√	√
	L22050	Collet Body 13N28 3/32 S9,20	pkg (5)	C	√	√	√
	L22051	Backcap Long 41V24 S9,20	each (1)	C	√	√	√
	L22052	Backcap Short 41V33 S9,20	each (1)	C	√	√	√
	L22053	Weldpro Wireless Foot Amperage Control 5-pin	each (1)	A	√	√	√
	L25005	Ground clamp Brass 300A	each (1)	A	√	√	√
	L23049	Ground clamp Brass 200A	each (1)	A	√	√	√
	L23052	Ground Clamp 300A with 15ft Cable and 35-50 connector	each (1)	A	√	√	√
	L23053	Electrode Holder 300A with 15ft Cable and 35-50 connector	each (1)	A	√	√	√
	L23054	Connector Dinse 35-50 Male	each (1)	A	√	√	√
	L23055	Connector Dinse 35-50 Female	each (1)	A	√	√	√
	L23057	Electrode Holder 300A	each (1)	A	√	√	√
	L25000	Flow Gauge Argon or Argon CO2 CGA 580	each (1)	A	√	√	√
	L25008	Welding Cart HD	each (1)	A		√	√
	L25009	Machine Protection Cover TIG200	each (1)	A		√	
	L25010	Weldpro Rotary Hand Amperage Control 5 pin 25'	each (1)	A	√	√	√
	L21004	Power Adaptor 115/230V	each (1)	A	√	√	√
	L23031	Ground Clamp 200A with 10ft Cable and 35-50 connector	each (1)	A	√	√	√
	L23002	Electrode holder 200A with 10ft Cable and 35-50 connector	each (1)	A	√	√	√

Picture	Torch	Part Number	Description	Unit Of. Measure	Class	CUT40HF	CUT60HF	CUT40NH	CUT60NH
		L21003	Ground Clamp 200A with 10' Cable and 10-25 connector disne	each (1)	A	✓	✓	✓	✓
		L21004	Power Adapter 115/230V	each (1)	A	✓	✓	✓	✓
		L23009	Ground Clamp Steel 200A	each (1)	A	✓	✓	✓	✓
	S45	L24000	CUT40NH Replacement Torch S45 PA0165G	each (1)	A	*		*	
	CB50	L24002	CUT40HF Replacement Torch CB50 PAE1301G	each (1)	A	*	*		
	CB70	L24003	CUT60HF Replacement Torch CB70 PAE1323G	each (1)	A				
	PT60	L24004	CUT60NH Replacement Torch PT60 PA2201G	each (1)	A				*
	S65	L24042	Replacement Torch S65 w/Central Adapter PA2200G	each (1)	A	**	**	**	**
	CB70	L24043	Replacement Torch CB70 w/Central Adapter PAE1322G	each (1)	A				
	S45	L24006	Electrode PR0110	pkg (5)	C			*	
	S45	L24007	Nozzle .030 (30A) PD0116-08	pkg (5)	C			*	
	S45 S65	L24009	Gas Diffuser/Swirl Ring PE0106	pkg (2)	C			✓	**
	S45	L24010	Outside Nozzle PC0116	pkg (2)	C	*		*	
	CB50	L24012	Electrode PR0017	pkg (5)	C	✓	✓		
	CB50 CB70	L24013	Gas Diffuser/Swirl Ring PE0007	pkg (2)	C	✓	✓		
	CB50 CB70	L24014	Nozzle .047 (70A) PD0088-12	pkg (5)	C	✓	✓		
	CB50 CB70	L24015	Nozzle .040 (50A) PD0088-10	pkg (5)	C	✓	✓		
	CB50 CB70	L24016	Nozzle .030 (40A) PD0088-08	pkg (5)	C	✓	✓		

Picture	Torch	Part Number	Description	Unit Of Measure	Class	CUT40HF	CUT60HF	CUT40NH	CUT60NH
	CB50	L24017	Outside Nozzle PC0003	pkg (2)	C	*			
	CB70	L24019	Electrode PR0063	pkg (5)	C	**	✓		
	CB70	L24020	Outside Nozzle PC0032	pkg (2)	C	**	✓		
	PT60	L24022	Outside Nozzle 60389	pkg (2)	C				*
	PT60	L24023	Gas Diffuser/Swirl Ring 30028	pkg (2)	C				*
	PT60	L24024	Electrode 52582	pkg (5)	C				*
	PT60	L24026	Nozzle (Pipe) .040 (50A) 51318.10	pkg (5)	C				*
	S45 CB70	L24032	Stand Off Spring CV0010	pkg (5)	C	**	✓	*	
	CB50	L24034	Stand Off Roller Leg CV0037	each (1)	C	*			
	CB70	L24038	Stand Off Double Pointed CV1117	pkg (2)	C	**	✓		
	S65	L24039	Stand Off Double Pointed CV1118	pkg (2)	C			**	**
	CB70	L24040	Air Flow Tube FH0211	pkg (2)	C	**	✓		
	CB50 CB70	L24050	Nozzle .043 (60A) PD0088-11	pkg (5)	C	✓	✓		
	S65	L24053	Electrode PR0098	pkg (5)	C			**	**
	S65	L24059	Nozzle .030 (40A) PD0098-08	pkg (5)	C			**	**
	S65	L24060	Nozzle.040 (60A) PD0098-10	pkg (5)	C			**	**
	CB70	L24035	Stand Off Roller Leg CV0073	each (1)	C	**	✓		
	CB70	L24041	Air Flow Tube LONG FH0215	pkg (2)	C	**	✓		

Picture	Torch	Part Number	Description	Unit Of Measure	Class	CUT40HF	CUT60HF	CUT40NH	CUT60NH
	CB50 CB70	L24046	Nozzle .040 (50A) LONG PD0063-10	pkg (5)	C	✓	✓		
	CB50 CB70	L24047	Nozzle .043 (60A) LONG PD0063-11	pkg (5)	C	✓	✓		
	CB50 CB70	L24048	Nozzle .047 (70A) LONG PD0063-12	pkg (5)	C	✓	✓		
	CB50 CB70	L24049	Nozzle .025 (20A) PD0088-06	pkg (5)	C	✓	✓		
	CB70	L24052	Electrode LONG PR0064	pkg (5)	C	**	✓		
	PT60	L24025	Nozzle (Pipe) .035 (40A) 51318.09	pkg (5)	C				*
	PT60	L24027	Nozzle (Flat) .043 (60A) 51313P.11	pkg (5)	C				*
	PT60	L24061	Stand Off Double Pointed 60432	pkg (2)	C				*
	S65	L24036	Stand Off Drag CV0298	pkg (2)	C			**	**
	S65	L24058	Outside Nozzle PC0098	pkg (2)	C			**	**
	S45	L24008	Nozzle .035 (40A) PD0116-09	pkg (5)	C			*	
	S45	L24033	Stand Off Roller Leg CV0024	each (1)	C			*	
	S65	L24054	Outside Nozzle DRAG PC0198	pkg(2)	C			**	**
	S65	L24055	Nozzle .030 (40A) DRAG PD0198-08	pkg(5)	C			**	**
	S65	L24056	Nozzle .040 (60A) DRAG PD0198-10	pkg(5)	C			**	**
	S65	L24057	Electrode DRAG PR0106	pkg(5)	C			**	**
	CB70	L24062	33 Piece Consumables Kit for CB70 Plasma Torch	each (1)	C	**	✓		
	S65	L24063	19 Piece Consumables Kit for S65 Plasma Torch	each (1)	C			**	**



USA HEADQUARTERS

1307 West Valley Highway North
Suite 103
Auburn, WA 98001
Main Office: 253-329-2179
Tech Support: 651-329-2686
URL: www.weldpro.com



WWW.WELDPRO.COM